Ei450



RadioLINK Alarm Controller



- Install as part of the system to get more control over your alarms
- Test, Locate and Silence functions
- RadioLINK+ Wireless interconnection
- 10 year Lithium battery powered
- LEDs for a visual display of Fire or Carbon Monoxide alarm activation

📀 RadioLINK®

Description

The Ei450 RadioLINK Alarm Controller is used to control all wirelessly interconnected fire and CO alarms from one location. It allows the user to remotely Test, Locate and Silence alarms in the system and is powered by a built-in 10 year lithium cell

Technical

RF Frequency (MHz) Indicators Technologies	868.499 Red - Fire, CO / Yellow - EoL RadioLINK	RF Range (m) Battery Type	>100 in free air Lithium primary
Dimensions & Weights			
Depth (mm)	27	Height (mm)	90
Width (mm)	90	Product weight (kg)	0.112
Packaged weight (kg)	0.178		
Approvals & Warranty			
Warranty	5 year warranty	EAN Number	5099383004731
Environmental			
Humidity Range (%)	15-95	Temperature Range (°C)	-10 to 40

T 01691 664100 E enquiries@aico.co.uk '

W www.aico.co.uk

Company Registration No.: 2544399 WEEE Registration No.: WEE/AE0109WY Battery Producer Registration No.: BPRN00307

