

Multi-Sensor Fire Alarm – Ei2110e



- Mains powered with back-up 10 year rechargeable lithium cells
- Contains both an optical and heat sensor for a total fire response
- Dust compensation – unique self-monitoring mechanism
- Is fully compatible with existing Aico systems
- Up to 12 Alarms and Devices can be interconnected
- Is simple to specify
- Provides intelligent fire detection
- Has an increased resistance to false alarms
- Is easier to install
- Is compatible with RadioLINK ⁺ interconnection and monitoring technology
- Is capable of alarm data extraction using AudioLINK [™] or whole system data extraction with RadioLINK ⁺
- Has a clean, modern design
- 10 Year life

FIT IN:



CONTAINS:



FOR WIRELESS INTERCONNECTION:

ADD Ei100MRF RadioLINK ⁺ Module



PRODUCT DESCRIPTION

The Ei2110e is a Multi-Sensor Fire Alarm that contains two separate sensing elements – optical and heat. Using intelligent software to monitor two different byproducts of fire, its response to all fire types (TF1 to TF6 & TF8) is vastly improved over traditional single sensor alarms. The new sensor chamber design intelligent software and the unique dust compensation algorithm also combine to reduce the frequency of nuisance alarms.

The Ei2110e runs on 230V AC mains power. In the event of mains failure, the 10 Year+ built in tamper-proof rechargeable lithium cells will provide back-up supply and continuous operation.

The AudioLINK [™] feature facilitates acoustic download of the Alarm parameters and status by using an App on your smartphone or tablet.

The Ei2110e also has hardwired and wireless (through the Ei100MRF) Remote Control capability, enabling it to be interconnected to and communicate with compatible Alarms and Devices. Up to 12 Alarms and Devices can be interconnected, which will cause all Alarms to sound when one unit senses fire. An interconnected system will enhance early detection and warning of fire.

The Ei2110e self-checks its sensors, battery voltage and internal circuitry every 40 seconds. Any fault condition found will be indicated by a combination of Red/ Amber LED flashes and/or audible beeps. The Ei2110e is designed with advanced diagnostics to help pre-warn of incumbent fault conditions.

The memory feature allows an Alarm that has previously activated to be easily identified.

TECHNICAL SPECIFICATION

- Sensor Type:** Optical & Thermistor Class A1
- Supply Voltage:** 230V AC, 50Hz
- Power Consumption:** 1W
- Battery back-up:** Rechargeable lithium cells
- Sound Level:** 85 dB(A) at 3 meters
- Temperature:** Operating - 0°C to 40°C
Storage - 0°C to 35°C (in a dry area)
- Humidity Range:** 0% to 90% Relative Humidity
- Button Test:** Simulates high temperature to check optical chamber, thermistor, electronics and horn
- Indicator LED's:** **Green** - Power
Red - Alarm or battery event
Amber - Fault event
- Memory:** Red LED will flash twice every 40 seconds indicating recent Alarm event
Pre-warn of incumbent fault conditions
- Diagnostics:** Enabled
- AudioLINK:** Enabled
- Insect Screen:** Prevents insects or debris entering chamber (1.00mm mesh size)
- Plastic material:** HIP UL 94 V0 Flame Retardant
- Dimensions:** Product - 150mm x 50mm
Package - 155mm x 155mm x 70mm
- Weight:** 346g (Boxed 412g)
- Warranty:** 5 year (limited) warranty
- Approvals:**

CE Kitemarked to
BS EN14604:2005
BS 5446-2:2003

Specifications are subject to change

Company Registration No. 2544399
WEEE Registration No. WEE/AE0109WY
Battery Producer Registration No. 2544399W



Rev2 03/2019 KTS