

Carbon Monoxide Alarm

Battery Powered

Model Ei205ENA

- Proven Electrochemical sensor
- Tamper Proof battery cover
- Memory feature records if Carbon Monoxide (CO) has been detected
- Easy to use Test/Hush button
- Pre alarm LED gives early warning of CO
- Advanced suppression and calibration technology
- Low power cell warning
- Loud distinctive alarm sound (85db (A) at 3 metres)
- Power, alarm and fault indicator lights
- Kitemarked to BS EN50291:2001
- 5 Year Guarantee



Product Description

The Ei205ENA is a Carbon Monoxide (CO) Alarm that runs on battery power. It has a sealed in tamper proof batteries designed to last 5 years (the life of the alarm).

The alarm has a high performance electrochemical sensor to sense CO presence.

The alarm has an integrated pattress and screws for easy wall or ceiling mounting.

Operation

- The green light will flash once every 40 seconds to show power is present.
- The alarm will sound and the red indicator will flash at different speeds to indicate the presence of various levels of CO gas (see overleaf).
- The alarm will beep every 40 seconds to indicate the battery is depleted and the unit needs replacing.
- The alarm will beep and the amber indicator will flash every 40 seconds to indicate a fault on the sensor.
- The 'Test/Hush' button will either silence false alarms (if briefly pressed) or perform a unit self test (if pressed and held). Note that the alarm cannot be silenced when sensing a CO level of 300ppm or above.
- Memory Feature—after the unit as been in alarm, the red indicator will flash every 40 seconds at a rate indicating the CO level previously detected.



Model Ei205ENA

Technical Specification

1. The CO Alarm carries the BSI Kitemark to indicate type testing to BS EN 50291:2001. It is CE marked to indicate conformance to BS EN 60065: 1994, BS EN 50081-1: 1992 and BS EN 50270: 1992 Safety and Electromagnetic Compatibility Directives.
2. New generation electrochemical cell type Carbon Monoxide sensor checks CO concentration every 50 seconds. Each unit is calibrated and tested in CO gas in order to ensure accuracy.
3. High level of selectivity. No false alarms when exposed to the following interference gases for 2 hours: (as per UL2034sec.38) Methane 500ppm, Butane 300ppm, Heptane 500ppm.
4. Battery powered; supplied with 3 long life alkaline AA batteries. Battery compartment is sealed to prevent unauthorised battery removal. The green LED on the cover will flash and alarm will beep to indicate if the unit needs replacement.
5. Tamperproof battery compartment - white locking rivets supplied.
6. Supplied with integral mounting base and fixing screws: suitable for ceiling or wall mounting.
7. Start up sequence - the green, red and amber LEDs will flash once, after 20 seconds the green LED will flash every 4 seconds for a further 45 seconds. The red LED will then flash once to indicate that the alarm is in full operation. Rapid warm up time - only 70 seconds to full operation.
8. Green LED power indicator light flashes once every 40 seconds to confirm integrity of battery power supply.
9. Low and high level indicators - red LED indicator light flashes every 2 seconds at 50ppm CO (sounder operates within 60-90 mins); flashes twice every second at 100ppm CO (sounder operates within 10-40 mins); flashes 4 times per second at 350ppm CO (sounder operates within 3 minutes)
10. Fault indicator - amber LED flashes and horn beeps every 40 seconds if a fault is detected.
11. Manual Test/Hush button - press and hold the Test/Hush button to test circuitry and horn. Pressing and releasing the Test/Hush button when the unit is sensing CO will silence the alarm for 4 minutes. It will only silence once until the gas clears. At 300ppm CO the unit cannot be silenced due to the increased danger.
12. Quick CO gas test - allows quick and easy testing of the unit with CO gas. Pressing the Test/Hush button causes the sensor to test for CO every 4 seconds. The unit automatically resets after approximately 3 minutes.
13. Memory feature - pressing the Test/Hush button records if CO has been detected during a period of absence: red LED off - no CO recorded; Red LED flashes twice (every 40 seconds) - 50ppm CO recorded, red LED flashes 4 times (every 40 seconds) - 100ppm, red LED flashes 8 times (every 40 seconds) - 300ppm CO recorded. Pressing the Test/Hush button for 20 seconds resets the memory.
14. Built in sounder to give a minimum output of 85dB(A) at 3 metres. Modulated sound output - 3 rapid pulses followed by a 1½ second pause, repeated until reset. This easily differentiates it from a typical smoke alarm.
15. Automatic reset of alarm test function and after an alarm state when CO gas clears.
16. Operating temperature range: -5°C to +40°C (23°F - 104°F). 15% to 95% relative humidity.
17. Dimensions: 135mm x 105mm x 42mm. Weight: 260g.
18. 5 year guarantee (covers the alarm and batteries).
19. Manufactured in Ireland.



Mile End Business Park, Oswestry, Shropshire SY10 8NN

Tel. 0870 758 4000

Fax. 0870 758 4010

www.aico.co.uk

E & OE Our policy is one of continuous improvement.

We reserve the right to amend designs and specifications without prior notice.

Ei205ENA DataSht Rev 0 2903.10

Aico Ltd is a wholly owned subsidiary of Ei Electronics



Europe's Leader in Residential Fire + Gas Detection
Ei Electronics, Shannon, Ireland



Made in
Ireland